

AE Indicators

Features

- » Vivid, backlit LCD easily visible in any lighting conditions
- » Capacity tracker built into display for easily monitoring possible overloads
- » Colour-coded keys facilitate quick recognition of the most frequently used buttons
- » User-selectable scale division
- » IP66 rated for protection against water and dust
- » Robust metal housing protects internal components in harsh environments
- » Hold function freezes the displayed weight, allowing time to lapse without losing the result
- » Checkweighing with audible alarm
- » Parts counting with preset sample sizes
- » Selectable digital filtering for animal/dynamic weighing delivers stable results for moving subjects
- » Wall-mount bracket for placing indicator on vertical surface
- » RS-232 interface for connection to computers and printers
- » Rechargeable battery included for operation virtually anywhere
- » AC adapter included
- » Programmable auto power-off to save energy



ADAM[®]

Applications

- » Weighing
- » Parts counting
- » Percentage weighing
- » Checkweighing
- » Dynamic / animal weighing

Model	AE 402
Capacity Range	Selectable
Resolution	1:80,000
Loadcell [Excitation Voltage]	5VDC
Loadcells [num]	4
Sensitivity	0.15uv/d
Zero Range	0-10mv
Signal Range	0-40mv
Weighing Units	g, kg, lb, lb:oz, oz, N
Stabilisation Time (sec)	2
Interface	RS-232
IP Rating	66
Calibration	External calibration
Display	Backlit LCD with 40mm-high digits
Power Supply	12VDC 800mA adapter / Internal rechargeable battery
Operating Temperature	0° to 40°C
Housing	Stainless steel
Overall Dim.	240x145x95mm (wxdxh)
Net Weight	2kg

Accessories

- » 1120011156 ATP Adam thermal printer
- » 3126011263 Thermal paper for item no. 1120011156-ATP printer
- » 3126011281 Thermal paper for item no. 1120011156-ATP printer (pack of 10)
- » 700400103 RS-232 Cable
- » 1100011297 AE402 Relay Box
- » 600002028 Adam DU data collection program

Scaletec S.A (PTY) LTD

Durban:
 Phone: +27 (0)31 564 8755
 Fax: +27 (0)31 564 1053
 Email: sales@scaletec-db.co.za

Capetown:
 Phone: +27 (0)21 982 0928
 Fax: +27 (0)21 982 4523
 Email: sales@scaletec-ct.co.za